















MATERIALS SPECIFICATIONS LINE

GRANITOKER

PRODUCT CHARACTERISTIC:

Supply of stain proof, frost proof, first grade, glazed and body coloured porcelain stoneware tiles, fully vitrified, in accordance with standards UNI EN 14411 ISO 13006 - Group B1a GL - with $\leq 0.1\%$ water absorption. Obtained by selected mixtures of clay, quartz and feldspars fired at 1250°C , type **Granitoker by Casalgrande Padana**, with surface textures ..., formats ..., thickness ..., colour ..., series ..., chosen by the works management for the following places:

TECHNICAL FEATURES:

  		STANDARDS	TEST RESULTS
	Product classification	UNI EN 14411 ISO 13006	B1a GL group fully vitrified
	Dimensional and surface quality	UNI EN ISO 10545-2	Very low tolerance
	Water absorption	UNI EN ISO 10545-3	$\leq 0,10\%$
	Flexural strength	UNI EN ISO 10545-4	N/mm^2 50-60
	Frost Resistance	All standards	Guaranteed
	Resistance to acids and alkalis with the exception of hydrofluoric acid	UNI EN ISO 10545-13	No damage
	Wear and abrasion resistance		High
	Linear thermal expansion	UNI EN ISO 10545-8	6×10^{-6}
	Slip resistance (Matt surface)	DIN 51130	See every series
	Light fastness	DIN 51094	No change of colours
	Stain resistance		Guaranteed